



# WHINFELL CLW 218

Kährs Luxury Tiles Click floor Whinfell has a spectrum of warm brown and grey tones inspired by cliffs of the archipelago. Whinfell, with its calm wood design and luxurious, natural impression gives any space a grand makeover.












## PRODUCT DETAILS

<b>Article Number</b>	LTCLW2004-218
<b>Dimensions</b>	218 x 1210 mm
<b>Weight per Package</b>	20.6 kg
<b>Area per Package</b>	2.1 m <sup>2</sup>
<b>Area per pallet</b>	84.5 m <sup>2</sup>
<b>Construction</b>	Click 6 mm

## FACTS

<b>Design</b>	Wood design
<b>Range</b>	Luxury Tiles
<b>Collection</b>	Breeze Collection
<b>Joint</b>	Click5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years residential/15 years commercial
<b>Thickness</b>	6 mm
<b>Installation method</b>	Floating

## TECHNICAL PROPERTIES

<b>Application</b>	EN ISO 10874	23/33/42	
<b>Effect of furniture leg</b>	EN ISO 16581	No visible damage/Change	
<b>Reaction To Fire</b>	EN13501-1	Bfl-s1	
<b>Thermal Resistance R-Value</b>		0.035 (m2K/W)	
<b>Residual indentation EN ISO 24343-1</b>		< 0.2 mm (*with underlayment)	
<b>Dimensional stability</b>	EN ISO 23999	< 0.1 %	
<b>Colour fastness</b>	EN ISO 105-B02	≥ 6	
<b>Slip resistance</b>	EN 13893	DS (>0.3)	
<b>Slip resistance</b>	DIN 51130	R10	
<b>Statical electrical propensity</b>	EN 1815	< 2 kV (antistatic)	
<b>Scratch resistance</b>	EN16094	Pass with good results	




## DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## TECHNICAL PROPERTIES

<b>Chemical resistance</b>	EN ISO 26987	Pass with good results	
<b>Effect of castor chair</b>	EN 425	Suitable	
<b>Resistance to bacteria and fungi</b>		Good	
<b>Impact sound reduction</b>	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
<b>Commercial usage classification</b>	EN 14354:2017	Class 33	

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



## Other products in this collection



Fontin - Click 6 mm



Hanmer - Click 6 mm



Whinfell - Click 6 mm



Yukon - Click 6 mm



Tiveden - Click 6 mm



Wentwood - Click 6 mm

### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*

